

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. - 14. (Canceled)

15. (Previously Presented) An electronic still camera comprising:

an image-capturing device that captures an image of a subject and outputs signals under first color coordinates comprising a plurality of color components;

an image processing device that performs image processing on the signals output from the image-capturing device; and

the image processing device including a color coordinate conversion unit that converts the signals output from the image-capturing device into signals under second color coordinates comprising a luminance component and color difference components, and a color difference signal correction unit that receives signals corresponding to the color difference components, and outputs corrected signals corresponding to the color difference components and a correction amount for a signal corresponding to the luminance component by using a two dimensional look-up table based upon the received signals corresponding to the color difference components,

wherein the two dimensional look-up table outputs the corrected signals corresponding to the color difference components and the correction amount for the signal corresponding to the luminance component when the received signals corresponding to the color difference components are input as arguments.

16. (Previously Presented) An electronic still camera according to claim 15, wherein the color coordinate conversion unit converts the signals under the first color coordinates into the signals under the second color coordinates by matrix calculation.

17. (Previously Presented) An electronic still camera according to claim 15, further comprising:

the image processing device including a luminance signal correction unit that corrects the signal corresponding to the luminance component with the correction amount and outputs a corrected signal corresponding to the luminance component;

a compression unit that compresses the corrected signal corresponding to the luminance component and the corrected signals corresponding to the color difference components to generate compressed image signals; and

a recording unit that records the compressed image signals.

18. (Previously Presented) An image processing method used in an electronic still camera, the method comprising:

capturing an image of a subject with an image-capturing device;

outputting signals under first color coordinates comprising a plurality of color components from the image-capturing device;

converting the signals output from the image-capturing device into signals under second color coordinates comprising a luminance component and color difference components; and

outputting corrected signals corresponding to the color difference components and a correction amount for a signal corresponding to the luminance component by using a two dimensional look-up table based upon the converted signals corresponding to the color difference components,

wherein the two dimensional look-up table outputs the corrected signals corresponding to the color difference components and the correction amount for the signal corresponding to the luminance component when the converted signals corresponding to the color difference components are input as arguments.

19. (Currently Amended) A computer-readable ~~computer program product~~
~~containing medium that stores~~ an image processing program ~~stored on a recording medium~~
for controlling an electronic still camera, the image processing program comprising
instructions to:

capture an image of a subject with an image-capturing device;

output signals under first color coordinates comprising a plurality of color
components from the image-capturing device;

convert the signals output from the image-capturing device into signals under
second color coordinates comprising a luminance component and color difference
components; and

output corrected signals corresponding to the color difference components and
a correction amount for a signal corresponding to the luminance component by using a two
dimensional look-up table based upon the converted signals corresponding to the color
difference components,

wherein the two dimensional look-up table outputs the corrected signals
corresponding to the color difference components and the correction amount for the signal
corresponding to the luminance component when the converted signals corresponding to the
color difference components are input as arguments.

20. (Previously Presented) An electronic still camera according to claim 15,
wherein when the two dimensional look up table does not store data corresponding to the
received signals, the color difference signal correction unit performs linear interpolation to
generate the data corresponding to the received signals.

21. (Canceled)